



Revision Number: 005.1

Issue date: 08/31/2016

**1. PRODUCT AND COMPANY IDENTIFICATION**

<b>Product name:</b>	<b>LOCTITE EA 3463 known as LOCTITE FM METAL MAGIC 40Z EN</b>	<b>IDH number:</b>	209681
<b>Product type:</b>	Epoxy stick	<b>Item number:</b>	98853
<b>Restriction of Use:</b>	None identified	<b>Region:</b>	United States
<b>Company address:</b>	<b>Contact information:</b>		
Henkel Corporation	Telephone: (860) 571-5100		
One Henkel Way	MEDICAL EMERGENCY Phone: Poison Control Center		
Rocky Hill, Connecticut 06067	1-877-671-4608 (toll free) or 1-303-592-1711		
	TRANSPORT EMERGENCY Phone: CHEMTREC		
	1-800-424-9300 (toll free) or 1-703-527-3887		
	Internet: www.henkelna.com		

**2. HAZARDS IDENTIFICATION**

**EMERGENCY OVERVIEW**

**DANGER:** CAUSES SKIN IRRITATION.  
MAY CAUSE AN ALLERGIC SKIN REACTION.  
CAUSES SERIOUS EYE DAMAGE.  
MAY CAUSE RESPIRATORY IRRITATION.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
SERIOUS EYE DAMAGE	1
SKIN SENSITIZATION	1
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3

**PICTOGRAM(S)**



**Precautionary Statements**

<b>Prevention:</b>	Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, eye protection, and face protection.
<b>Response:</b>	IF ON SKIN: Wash with plenty of water. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing.
<b>Storage:</b>	Store in a well-ventilated place. Keep container tightly closed. Store locked up.
<b>Disposal:</b>	Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

**See Section 11 for additional toxicological information.**

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Talc	14807-96-6	30 - 60
Iron	7439-89-6	10 - 30
Epoxy resin	Proprietary	10 - 30
Glass, oxide, chemicals	65997-17-3	10 - 30
Polyether polymercaptan	Unknown	5 - 10
Substituted aminophenol	Proprietary	5 - 10
Treated fumed silica	67762-90-7	1 - 5
Quartz (SiO <sub>2</sub> )	14808-60-7	0.1 - 1

\* Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

### 4. FIRST AID MEASURES

<b>Inhalation:</b>	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
<b>Skin contact:</b>	Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.
<b>Eye contact:</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
<b>Ingestion:</b>	DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention.
<b>Symptoms:</b>	See Section 11.

### 5. FIRE FIGHTING MEASURES

<b>Extinguishing media:</b>	Water spray (fog), foam, dry chemical or carbon dioxide.
<b>Special firefighting procedures:</b>	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
<b>Unusual fire or explosion hazards:</b>	In case of fire, keep containers cool with water spray. Closed containers may rupture (due to build up of pressure) when exposed to extreme heat.
<b>Hazardous combustion products:</b>	Oxides of carbon. Oxides of sulfur. Halogenated compounds. Metal oxide fumes. Irritating vapors.

### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

<b>Environmental precautions:</b>	Do not allow product to enter sewer or waterways.
<b>Clean-up methods:</b>	Remove all sources of ignition. Evacuate and ventilate spill area; dike spill to prevent entry into water system; wear full protective equipment during clean-up. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up as much material as possible. Store in a partly filled, closed container until disposal.

## 7. HANDLING AND STORAGE

**Handling:** Use only with adequate ventilation. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Keep container closed. Refer to Section 8.

**Storage:** For safe storage, store at or below 32 °C (89.6 °F) Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials. Store away from heat, sparks, flames, or other sources of ignition. Protect from direct sunlight.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Talc	2 mg/m3 TWA Respirable fraction.	20 MPPCF TWA 2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable. 0.3 mg/m3 TWA Total dust.	None	50 ppm
Iron	None	None	None	None
Epoxy resin	None	None	None	None
Glass, oxide, chemicals	0.2 FIBERS/CM3 TWA Fiber. 10 mg/m3 TWA Inhalable dust. 1 FIBERS/CM3 TWA Fiber. 3 mg/m3 TWA Respirable fraction. 1 FIBERS/CM3 TWA Fiber. 5 mg/m3 TWA Inhalable fraction. 1 FIBERS/CM3 TWA Fiber.	15 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction.	None	None
Polyether polymercaptan	None	None	None	None
Substituted aminophenol	None	None	None	None
Treated fumed silica	10 mg/m3 TWA Inhalable dust. 3 mg/m3 TWA Respirable fraction.	15 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction.	None	None
Quartz (SiO <sub>2</sub> )	0.025 mg/m3 TWA Respirable fraction.	2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable. 0.05 mg/m3 PEL	None	None

**Engineering controls:** Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

**Respiratory protection:** Use a NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists.

**Eye/face protection:** Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.

**Skin protection:**

Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact. Neoprene, Butyl-rubber, or nitrile-rubber gloves.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state:</b>	Putty
<b>Color:</b>	Metallic, Black
<b>Odor:</b>	Mercaptan, Sulfur
<b>Odor threshold:</b>	Not available.
<b>pH:</b>	Not applicable
<b>pH:</b>	Not applicable
<b>Vapor pressure:</b>	Not determined
<b>Boiling point/range:</b>	Not available.
<b>Melting point/ range:</b>	Not applicable
<b>Specific gravity:</b>	2.247
<b>Vapor density:</b>	Not applicable
<b>Flash point:</b>	Not available.
<b>Flammable/Explosive limits - lower:</b>	Not applicable
<b>Flammable/Explosive limits - upper:</b>	Not applicable
<b>Autoignition temperature:</b>	Not applicable
<b>Flammability:</b>	Not applicable
<b>Evaporation rate:</b>	Not applicable
<b>Solubility in water:</b>	Insoluble
<b>Partition coefficient (n-octanol/water):</b>	Not available.
<b>VOC content:</b>	< 1 %
<b>Viscosity:</b>	Not available.
<b>Decomposition temperature:</b>	Not available.

## 10. STABILITY AND REACTIVITY

<b>Stability:</b>	Stable under normal conditions of storage and use.
<b>Hazardous reactions:</b>	None under normal processing.
<b>Hazardous decomposition products:</b>	Oxides of carbon. Oxides of sulfur. Halogenated compounds. Metal oxide fumes. Irritating vapors.
<b>Incompatible materials:</b>	None identified.
<b>Reactivity:</b>	Not available.
<b>Conditions to avoid:</b>	Elevated temperatures. Protect from direct sunlight. Heat, flames, sparks and other sources of ignition. Store away from incompatible materials.

## 11. TOXICOLOGICAL INFORMATION

**Relevant routes of exposure:** Skin, Inhalation, Eyes, Ingestion

### Potential Health Effects/Symptoms

**Inhalation:** May cause respiratory tract irritation. Inhalation of vapors or mists of the product may be irritating to the respiratory system. Contains crystalline silica (quartz), which is classified as a possible carcinogen. However, the crystalline silica present in this product is encapsulated in the liquid and will only be liberated if the product is sanded or abraded, and even then what is liberated will not be pure crystalline silica. Appropriate precautions, however, should be taken if the product is sanded or abraded to prevent personnel from breathing the dust.

**Skin contact:** Causes allergic skin reaction.

**Eye contact:** Causes serious eye damage.

**Ingestion:** May cause gastrointestinal tract irritation if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Talc	None	Irritant, Lung, Some evidence of carcinogenicity
Iron	None	Eyes, Lung
Epoxy resin	None	Allergen, Irritant
Glass, oxide, chemicals	None	Allergen, Respiratory
Polyether polymercaptan	None	No Data
Substituted aminophenol	None	Irritant, Allergen
Treated fumed silica	None	Irritant
Quartz (SiO <sub>2</sub> )	None	Immune system, Lung, Some evidence of carcinogenicity

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Talc	No	Group 2B	No
Iron	No	No	No
Epoxy resin	No	No	No
Glass, oxide, chemicals	Reasonably Anticipated to be a Human Carcinogen.	Group 2B	No
Polyether polymercaptan	No	No	No
Substituted aminophenol	No	No	No
Treated fumed silica	No	No	No
Quartz (SiO <sub>2</sub> )	Known To Be Human Carcinogen.	Group 1	No

## 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Follow all local, state, federal and provincial regulations for disposal.

**Hazardous waste number:** Not a RCRA hazardous waste.

## 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

### U.S. Department of Transportation Ground (49 CFR)

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

**International Air Transportation (ICAO/IATA)**

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

**Water Transportation (IMO/IMDG)**

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

<b>15. REGULATORY INFORMATION</b>
-----------------------------------

**United States Regulatory Information**

**TSCA 8 (b) Inventory Status:** All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.  
**TSCA 12 (b) Export Notification:** None above reporting de minimis  
**CERCLA/SARA Section 302 EHS:** None above reporting de minimis.  
**CERCLA/SARA Section 311/312:** Immediate Health, Delayed Health  
**CERCLA/SARA Section 313:** None above reporting de minimis.  
**California Proposition 65:** This product contains a chemical known in the State of California to cause cancer.

**Canada Regulatory Information**

**CEPA DSL/NDSL Status:** All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

<b>16. OTHER INFORMATION</b>
------------------------------

**This safety data sheet contains changes from the previous version in sections:** New Safety Data Sheet format.

**Prepared by:** Rebecca Coons, Regulatory Affairs Specialist

**Issue date:** 08/31/2016

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.